

# Move Shipment Request Manual

1.0.0

---

## Data

## Section: 1.1

Name:	data
Full Path:	moveShipmentRequest.data
Type:	String Value
Is Required?:	Yes
Minimum Length:	
Maximum Length:	

### Sample JSON:

```
"data": "MOVE_SHIPMENT_REQUEST"
```

### Description:

- Specifies type of message. For requeue request must be exactly "MOVE\_SHIPMENT\_REQUEST"

---

## Send Id

Section: 1.2

Name:	sendId
Full Path:	moveShipmentRequest.sendId
Type:	String Value
Is Required?:	No
Minimum Length:	1
Maximum Length:	68

### Sample JSON:

```
"sendId": "001"
```

### Description:

- Unique ID assigned by the software integrating with BorderConnect.
- Will be quoted in server responses related to your JSON upload.
- e.g. if this is an ACE Trip Create operation, the server response advising the success or failure of the create will quote the value you provide in this field.
- This field is never required, nor will any validation prevent you from duplicating send IDs.

---

## Company Key

Section: 1.3

Name:	companyKey
Full Path:	moveShipmentRequest.companyKey
Type:	String Value
Is Required?:	No
Minimum Length:	1
Maximum Length:	30

### Sample JSON:

```
"companyKey": "c4555-45983943tr9"
```

### Description:

- Used when connected as a service provider to identify which company account the move shipment request pertains to.
- Must exactly match company key for the account.
- Mandatory when connected as a service provider. Will be ignored otherwise.

---

## Attach ACE Shipments

Section: 1.4

Name:	attachAceShipments
Full Path:	moveShipmentRequest.attachAceShipments
Type:	Object
Is Required?:	No

### Sample JSON:

```
"attachAceShipments": {  
  "tripNumber": "TEST0001",  
  "shipmentControlNumbers": [  
    "TESTPAPS00012345",  
    "TESTPAPS00012346"  
  ]  
}
```

### Description:

- Used to specify a list of unassociated ACE shipments to attach to an ACE trip.

---

## Trip Number

Section: 1.4.1

Name:	tripNumber
Full Path:	moveShipmentRequest.attachAceShipments.tripNumber
Type:	String Value
Is Required?:	Yes
Minimum Length:	8
Maximum Length:	25

### Sample JSON:

```
"tripNumber": "TEST0001"
```

### Description:

- The trip number that the list of ACE shipments should be attached to.

---

## Shipment Control Numbers

Section: 1.4.2

Name:	shipmentControlNumbers
Full Path:	moveShipmentRequest.attachAceShipments.shipmentControlNumbers
Type:	Array<String>
Is Required?:	Yes
Minimum Length (of element in array):	8
Maximum Length (of element in array):	16
Minimum Items (of elements in array):	1
Maximum Items (of elements in array):	9999

### Sample JSON:

```
"shipmentControlNumbers": [ "TESTPAPS00012345", "TESTPAPS00012346" ]
```

### Description:

- List of shipment control numbers pertaining to ACE shipments to be attached to specified ACE trip.

---

## Detach ACE Shipments

Section: 1.5

Name:	detachAceShipments
Full Path:	moveShipmentRequest.detachAceShipments
Type:	Object
Is Required?:	No

### Sample JSON:

```
"detachAceShipments": {  
  "tripNumber": "TEST0001",  
  "shipmentControlNumbers": [  
    "TESTPAPS00012345",  
    "TESTPAPS00012346"  
  ]  
}
```

### Description:

- Used to specify a list of ACE shipments to detach from an ACE trip.



---

## Trip Number

Section: 1.5.1

Name:	tripNumber
Full Path:	moveShipmentRequest.detachAceShipments.tripNumber
Type:	String Value
Is Required?:	Yes
Minimum Length:	8
Maximum Length:	25

### Sample JSON:

```
"tripNumber": "TEST0001"
```

### Description:

- The trip number that the list of ACE shipments should be detached from.

---

## Shipment Control Numbers

Section: 1.5.2

Name:	shipmentControlNumbers
Full Path:	moveShipmentRequest.detachAceShipments.shipmentControlNumbers
Type:	Array<String>
Is Required?:	Yes
Minimum Length (of element in array):	8
Maximum Length (of element in array):	16
Minimum Items (of elements in array):	0
Maximum Items (of elements in array):	9999

### Sample JSON:

```
"shipmentControlNumbers": [ "TESTPAPS00012345", "TESTPAPS00012346" ]
```

### Description:

- List of shipment control numbers pertaining to ACE shipments to be detached from specified ACE trip.
- If left empty or not provided, all ACE shipments on specified ACE trip will be detached.

---

## Attach ACI Shipments

Section: 1.6

Name:	attachAciShipments
Full Path:	moveShipmentRequest.attachAciShipments
Type:	Object
Is Required?:	No

### Sample JSON:

```
"attachAciShipments": {  
  "tripNumber": "12345677",  
  "cargoControlNumbers": [  
    "1234PARS00012345",  
    "1234PARS00012346"  
  ]  
}
```

### Description:

- Used to specify a list of unassociated ACI shipments to attach to an ACI trip.

---

## Trip Number

Section: 1.6.1

Name:	tripNumber
Full Path:	moveShipmentRequest.attachAciShipments.tripNumber
Type:	String Value
Is Required?:	Yes
Minimum Length:	8
Maximum Length:	25

### Sample JSON:

```
"tripNumber": "12345677"
```

### Description:

- The trip number that the ACI shipments should be attached to.

---

## Cargo Control Numbers

Section: 1.6.2

Name:	cargoControlNumbers
Full Path:	moveShipmentRequest.attachAciShipments.cargoControlNumbers
Type:	Array<String>
Is Required?:	Yes
Minimum Length (of element in array):	8
Maximum Length (of element in array):	25
Minimum Items (of elements in array):	1
Maximum Items (of elements in array):	2000

### Sample JSON:

```
"cargoControlNumbers": [ "1234PARS00012345", "1234PARS00012346" ]
```

### Description:

- List of shipment control numbers pertaining to ACI shipments to be attached to specified ACI trip.

---

## Detach ACI Shipments

Section: 1.7

Name:	detachAciShipments
Full Path:	moveShipmentRequest.detachAciShipments
Type:	Object
Is Required?:	No

### Sample JSON:

```
"detachAciShipments": {  
  "tripNumber": "12345677",  
  "cargoControlNumbers": [  
    "1234PARS00012345",  
    "1234PARS00012346"  
  ]  
}
```

### Description:

- Used to specify a list of ACI shipments to detach from an ACI trip.

---

## Trip Number

Section: 1.7.1

Name:	tripNumber
Full Path:	moveShipmentRequest.detachAciShipments.tripNumber
Type:	String Value
Is Required?:	Yes
Minimum Length:	8
Maximum Length:	25

### Sample JSON:

```
"tripNumber": "12345677"
```

### Description:

- The trip number that the ACI shipments should be detached from.

---

## Cargo Control Numbers

Section: 1.7.2

Name:	cargoControlNumbers
Full Path:	moveShipmentRequest.detachAciShipments.cargoControlNumbers
Type:	Array<String>
Is Required?:	Yes
Minimum Length (of element in array):	8
Maximum Length (of element in array):	25
Minimum Items (of elements in array):	0
Maximum Items (of elements in array):	2000

### Sample JSON:

```
"cargoControlNumbers": [ "1234PARS00012345", "1234PARS00012346" ]
```

### Description:

- List of shipment control numbers pertaining to ACI shipments to be detached from specified ACI trip.
- If left empty or not provided, all ACI shipments on specified ACI trip will be detached.